

# SERIAL INPUT

AE SERIES - OPTION 354

## RS232 or RS485 SERIAL INPUT



**Up to 2000 Feet on  
2-conductor cable**



**Send time or data to multiple displays throughout your facility.  
Ideal for computer or master clock controlled clock systems, timers,  
process indicators, and World Time Zone Clock displays.**

Multi-drop, multi-address, multi-mode:

12/24 hour time, up / down elapsed time, ASCII, and number modes.

Two wire system - easily connects to PLC's, computers, master clocks, multi-media systems, and AE21 Display Controllers. Connect up to 50 AE devices to a standard RS232 port, up to 2000 feet away. Expand the number of devices and the distance using the AE-455DR6, Six Channel RS232 Driver.

Keeps time and retains last data sent during power outages.

Available for all 2, 3, 4, 5, and 6 digit *AE Series Displays*

*AE SERIES DISPLAYS* are available with: 1", 2.3", 4", 8", and 12" High Digits.

**Visible from 5 feet to 500 feet away...**

**TWO YEAR WARRANTY**



**APPLIED  
TECHNICAL  
SYSTEMS**

**800-444-7161**

BOX 5705 • SHREVEPORT, LOUISIANA. 71135 • (318) 797-7508

FAX: 318-797-4864  
www.ats-usa.com

## DESCRIPTION

Option 354 provides an Intelligent Serial Input for the AE Series Displays. This is not a standard RS232 input. However, up to 50 AE Series Devices with this option can be connected to a standard RS232 port, at distances up to 2000 feet away. Signal drivers are available to provide systems with unlimited numbers of displays. This option allows AE Series Displays to communicate with host computers, process computers (PLC's), multi-media system controllers, and other equipment with RS232 ports. Applications include computer controlled master clock systems, time zone clocks, time to next show timers, process indicators, and message displays.

A simple 10 Byte message is required to send data or control information to the display. It provides addressing, mode selection, six characters of data, and display attributes.

## SPECIFICATIONS

INPUT:	TWO WIRE SYNCHRONOUS (RECEIVE ONLY) RS232 OR OPTIONAL RS485. 2400 BAUD, NO PARITY, 8 DATA BITS, 1 STOP BIT.
CONTROL:	TEN BYTE MESSAGE:
BYTE 0:	START CHARACTER - 11H
BYTE 1:	ADDRESS BYTE - RANGE IS 0 TO 15 (OPTIONAL 0-255). ADDRESS 0 PROVIDES AN ALL CALL.
BYTE 2:	MODE BYTE - RANGE IS 0 TO 255. SELECTS DISPLAY FUNCTION. USES BYTES 3 TO 8 AS INPUT DATA. SOME OF THE MODES INCLUDED:
	MODE 0      ASCII CHARACTER MODE.
	MODE 1      NUMBER MODE.
	MODE 2      GRAPHIC CHARACTER MODE.
	MODE 3      12 HOUR TIME / TIMER MODE.
	MODE 4      24 HOUR TIME / TIMER MODE.
	MODE 5      COUNT DOWN TIMER MODE.
	MODE 6      DISPLAYS SOFTWARE VERSION
	MODE 7      DAYCOUNTER
BYTES 3 TO 8:	SIX CHARACTER BYTES - DISPLAY DATA OR SETTINGS FOR THE MODE SELECTED IN BYTE 2.
BYTE 9:	MISCELLANEOUS DIGIT BYTE - PROVIDES COLONS, AM/PM INDICATORS, AND OTHER DISPLAY ATTRIBUTES.
BATTERY:	RECHARGEABLE NI-CAD BATTERY BACK-UP KEEPS TIME OR RETAINS THE LAST DATA SENT DURING POWER OUTAGES.

## ORDERING INFORMATION

Most AE Series Displays are configured to your specifications at the time of your order. Their modular design allows them to be constructed from Off-The-Shelf components and assemblies in quick order.

Choose the desired type, size, number of digits, and other requirements from the AE Series Large Display brochure. Adding "354" to the end of the model number indicates the RS232 Serial Input option is installed.

**FOR ASSISTANCE CALL 800-444-7161**