



- Economical brass construction with aluminum housing
- Large 6" Dial Face
- Pressures up to 10,000 PSIG
- ± 1.0 % accuracy



KOBOLD DRG64 Pressure Gauge

With its six inch face, the DRG64 pressure gauge is readily visible from across a room. An aluminum housing, copper bourdon tube element, and brass movement combine to keep the DRG64 affordable. Accuracy is kept at an uncompromising ±1.0% of full scale.

Mounting options abound: freestanding with fittings at either the bottom or rear, as well as rear fitting panel mountable versions. The panel mountable versions come in two styles; one bezel is fastened via screws, while the other uses a rear pressure bracket.

Pulsation and vibration in the medium may be accommodated with an optional glycerin filling for the indicator mechanism.

Specifications

Ranges: -14.7 to 10,000 PSIG (see table)

Over Pressure Protection
Momentary: 1.15 to 1.3 x range max.

Sensing Element: bourdon tube

Accuracy: ±1.0% of full scale

Operating Temperature
Medium: freezing to 180°F
Ambient: freezing to 140°F

Fittings: 1/2" NPT

Materials of Construction

Wetted Parts:
Element
< 1000 PSIG: Copper
1000 PSIG & Up: Stainless Steel
Fitting: Cu Alloy

Exterior
Movement: Brass
Housing: Aluminum

Bezel
Standard: Aluminum
DRG64-4xxx: Chrome plated Al
Pointer: Black aluminum
Indicator Dial: White aluminum
Window: Plexiglass

Options: Glycerin damped indicator assembly



6" BRASS BOURDON TUBE PRESSURE GAUGE

DRG64 Ordering Information

DRG64 = Copper Element High Pressure Bourdon Tube Pressure Gauge

- 1 = 160 mm (6 inch) Dial Face, Bottom Process Connection
- 2 = 160 mm (6 inch) Dial Face, Rear Process Connection
- 3 = 160 mm (6 inch) Dial Face, Rear Process Connection with Flange Style Panel Mountable Bezel
- 4 = 160 mm (6 inch) Dial Face, Rear Process Connection with Compression Mountable Bezel

Range = Pressure Range Abbreviation

H00 = -30" to 0" Hg	210 = 100 PSIG	260 = 600 PSIG	350 = 5000 PSIG
115 = 15 PSIG	216 = 160 PSIG	310 = 1000 PSIG	410 = 10000 PSIG
130 = 30 PSIG	220 = 200 PSIG	320 = 2000 PSIG	
160 = 60 PSIG	230 = 300 PSIG	330 = 3000 PSIG	

Available Measuring Ranges

F = Glycerin damped indicator assembly

Options

DRG64 -4 216 F Sample DRG64 Specification

Dimensions (mm)

